CERTI-LABEL PRODUCTS

CERTI-LABEL CEDAR SHAKES

Certi-Split[®] Handsplit Shakes



CERTI-SPLIT PREMIUM GRADE dar Shakes

Certi-Sawn[®] Tapersawn Shakes



Certi-Split[®] Tapersplit



These shakes are sawn both sides. Premium and Number 1 Grades are the **CERTI-SAWN** most common. Premium Grade is 100% edge grain, 100% clear and 100% PREMIUM GRADE heartwood. Number 1 Grade allows up to 20% flat grain in each bundle. ad Cedar Shake

> Produced by hand, using a sharp bladed steel froe and a mallet. The natural shingle-like taper is achieved by reversing the block, end-for-end, with each split. Premium Grade only.

These shakes have split faces and sawn backs. Cedar logs are first cut into

diagonally through a bandsaw to produce two tapered shakes from each

(Up to 20% flat grain allowed in each bundle).

Number 2 and 3 Grades are also available.

blank. Available in Premium Grade (100% edge grain) or Number 1 Grade

desired lengths. Blanks or boards of proper thickness are split and then run

Certi-Split[®] Straight-Split



Produced by machine or in the same manner as tapersplit shakes except that by splitting from the same end of the block, the shakes acquire the same thickness throughout. Premium Grade only.

CERTIGRADE[®] CEDAR SHINGLES

Number 1 Blue Label



CERTIGRADE Red Cedar Shingles

The premium grade of shingles for roofs and sidewalls. These top-grade shingles are 100% heartwood, 100% clear and 100% edge grain. Available in 16" or 18" or 24" lengths.

Number 2 Red Label



Number 3 Black Label



Number 4 Undercoursing





CEDAR SHAKE & SHINGLE B

A good grade for many applications. Not less than 10" clear on 16" shingles, 11" clear on 18" shingles and 16" clear on 24" shingles. Flat grain and limited sapwood are permitted in this grade.



A utility grade for economy applications and secondary buildings. Not less than 6" clear on 16" and 18" shingles, 10" clear on 24" shingles.

CERTIGRADE **Red Cedar Shingles** Recommended for Undercoursing o Double-Coursed Sidewalls only CEDAR SHAKE & SHINGLE BUREAU THE RECOMPTO ADMINISTRATION

A utility grade for undercoursing of double coursed sidewalls only. Not a roofing material and not to be used as a starter course for roofs.